

DC Fans



Xprovider Technology
Model: 4010 Series

- Fan Size: 40 x 40 x 10 mm
- Frame Material: Plastic P.B.T. UL 90V-0.
- Fan Blade Material: Plastic P.B.T. UL 90V-0.
- Lead Wire: UL 1007 AWG#24"1/2" Red"1/2" Black.
- Bearing Type: Precision Ball or Quality sleeve.
- Application: Computer, Consumer Electronics.



Performance Curves

Dimensions Unit: mm



Specification:

Model	Rated Voltage	Operating Voltage	Rated Current	Input Power	Air Flow	Static Pressure	Speed	Noise	Weight
4008H2H	12VDC	9~14VDC	0.09A	1.08W	12.60CFM	2.95mm	5000RPM	25db	20g
4008H2M	12VDC	9~14VDC	0.06A	0.72W	25.60CFM	2.95mm	5000RPM	25db	20g
4008H2L	12VDC	9~14VDC	0.05A	0.60W	31.12CFM	1.65mm	6000RPM	25db	20g

Option: 24VDC Available

DC Fans


Xprovider Technology

Model: 4020 Series


- Fan Size: 40 x 40 x 20 mm
- Frame Material: Plastic P.B.T. UL 94V-0.
- Fan Blade Material: Plastic P.B.T. UL 94V-0.
- Lead Wire: UL 1007 AWG#24"1/2" Red"1" Black.
- Bearing Type: Precision Ball or Quality sleeve.
- Application: Computer, Consumer Electronics.



Performance Curves



Dimensions Unit: mm



Specification:

Model	Rated Voltage	Operating Voltage	Rated Current	Input Power	Air Flow	Static Pressure	Speed	Noise	Weight
4020H2H	12VDC	9-14VDC	0.09A	1.08W	5.16CFM	1.36mm	5000RPM	27dB	25g
4020H2M	12VDC	9-14VDC	0.07A	0.84W	5.12CFM	1.43mm	5000RPM	25dB	25g
4020H2L	12VDC	9-14VDC	0.06A	0.72W	4.03CFM	1.22mm	4000RPM	24dB	25g

Option: 24VDC Available

DC Fans


Xprovider Technology

Model: 5010 Series


- Fan Size: 50 x 50 x 10 mm
- Frame Material: Plastic P.B.T. UL 90V-0.
- Fan Blade Material: Plastic P.B.T. UL 90V-0.
- Lead Wire: UL 1007 AWG#24 1/2' Red 1/2' Black.
- Bearing Type: Precision Ball or Quality sleeve.
- Application: Computer, Consumer Electronics.



Performance Curves



Dimensions Unit: mm



Specification:

Model	Rated Voltage	Operating Voltage	Rated Current	Input Power	Air Flow	Static Pressure	Speed	Noise	Weight
500812H	12VDC	9~14VDC	0.10A	1.20W	12.25CFM	2.75mm	5000RPM	25db	15g
500812M	12VDC	9~14VDC	0.08A	0.96W	11.25CFM	2.45mm	4500RPM	27db	15g
500812L	12VDC	9~14VDC	0.06A	0.72W	10.00CFM	2.05mm	4000RPM	25db	15g

Option: 24VDC Available

DC Fans

Xprovider Technology


Model: S015 Series

- Fan Size: 50 x 50 x 15 mm
- Frame Material: Plastic P.B.T. UL 90V-0.
- Fan Blade Material: Plastic P.B.T. UL 90V-0.
- Lead Wire: UL 1007 AWG#24"1/2" Red"1" Black.
- Bearing Type: Precision Ball or Quality sleeve.
- Application: Computer, Consumer Electronics.



Performance Curves

Dimensions Unit: mm



Specification:

Model	Rated Voltage	Operating Voltage	Rated Current	Input Power	Air Flow	Static Pressure	Speed	Noise	Weight
S0151H	12VDC	9~14VDC	0.16A	1.97W	12.62CFM	1.2mm	5000RPM	16db	25g
S0151M	12VDC	9~14VDC	0.14A	1.68W	9.46CFM	1.0mm	4500RPM	13db	25g
S0151L	12VDC	9~14VDC	0.12A	1.44W	6.97CFM	0.7mm	4000RPM	10db	25g

Option: 24VDC Available


DC Fans

Xprovider Technology
Model: 6010 Series


- Fan Size: 60 x 60 x 10 mm
- Frame Material: Plastic P.B.T. UL 94V-0.
- Fan Blade Material: Plastic P.B.T. UL 94V-0.
- Lead Wire: UL 1007 AWG#24 1/2' Red 1/2' Black.
- Bearing Type: Precision Ball or Quality sleeve.
- Application: Computer, Consumer Electronics.



Performance Curves



Dimensions Unit: mm



Specification:

Model	Rated Voltage	Operating Voltage	Rated Current	Input Power	Air Flow	Static Pressure	Speed	Noise	Weight
600H2H	12VDC	9-14VDC	0.30A	3.60W	18.75CFM	3.21mm	4500RPM	25db	24g
600H2M	12VDC	9-14VDC	0.24A	2.88W	15.24CFM	2.57mm	3600RPM	26db	24g
600H2L	12VDC	9-14VDC	0.16A	1.92W	12.57CFM	2.01mm	3000RPM	25db	24g

Option: 24VDC Available

DC Fans


Xprovider Technology

Model: 6015 Series


- Fan Size: 60 x 60 x 15 mm
- Frame Material: Plastic P.B.T. UL 94V-0.
- Fan Blade Material: Plastic P.B.T. UL 94V-0.
- Lead Wire: UL 1007 AWG#24 1/2' Red 1/2' Black.
- Bearing Type: Precision Ball or Quality sleeve.
- Application: Computer, Consumer Electronics.



Performance Curves



Dimensions Unit: mm



Specification:

Model	Rated Voltage	Operating Voltage	Rated Current	Input Power	Air Flow	Static Pressure	Speed	Noise	Weight
600512H	12VDC	10-14VDC	0.36A	1.18W	12.61CFM	0.35mm	4000RPM	15db	15g
600512M	12VDC	10-14VDC	0.20A	2.40W	19.60CFM	2.35mm	6000RPM	16db	15g
600512L	12VDC	10-14VDC	0.15A	1.80W	16.79CFM	2.35mm	12000RPM	27db	15g

Option: 24VDC Available

DC Fans


Xprovider Technology
Model: 6020 Series

- Fan Size: 60 x 60 x 20 mm
- Frame Material: Plastic P.B.T. UL 94V-0.
- Fan Blade Material: Plastic P.B.T. UL 94V-0.
- Lead Wire: UL 1007 AWG#24" 1/2' Red 1/2' Black.
- Bearing Type: Precision Ball or Quality sleeve.
- Application: Computer, Consumer Electronics.



Performance Curves

Dimensions Unit: mm



Specification:

Model	Rated Voltage	Operating Voltage	Rated Current	Input Power	Air Flow	Static Pressure	Speed	Noise	Weight
6020H2H	12VDC	9~14VDC	0.18A	2.16W	20.77CFM	5.51mm	4500RPM	25db	30g
6020H2M	12VDC	9~14VDC	0.15A	1.80W	17.12CFM	5.01mm	4000RPM	26db	30g
6020H2L	12VDC	9~14VDC	0.12A	1.44W	14.18CFM	2.87mm	3500RPM	22db	30g

Option: 24VDC Available

DC Fans


Xprovider Technology

Model: 6025 Series


- Fan Size: 60 x 60 x 25 mm
- Frame Material: Plastic P.B.T. UL 94V-0.
- Fan Blade Material: Plastic P.B.T. UL 94V-0.
- Lead Wire: UL 1007 AWG#24 1/2' Red 1/2' Black.
- Bearing Type: Precision Ball or Quality sleeve.
- Application: Computer, Consumer Electronics.



Performance Curves



Dimensions Unit: mm



Specification:

Model	Rated Voltage	Operating Voltage	Rated Current	Input Power	Air Flow	Static Pressure	Speed	Noise	Weight
602512H	12VDC	9-14VDC	0.18A	2.16W	25.8CFM	5.96mm	4500RPM	25db	14g
602512M	12VDC	9-14VDC	0.15A	1.80W	22.9CFM	4.85mm	4000RPM	27db	14g
602512L	12VDC	9-14VDC	0.12A	1.44W	18.1CFM	3.91mm	3500RPM	24db	14g

Option: 24VDC Available

DC Fans


Xprovider Technology
Model: 7015 Series

- Fan Size: 70 x 70 x 15 mm
- Frame Material: Plastic P.B.T. UL 94V-0.
- Fan Blade Material: Plastic P.B.T. UL 94V-0.
- Lead Wire: UL 1007 AWG#24"1/2" Red"1" Black.
- Bearing Type: Precision Ball or Quality sleeve.
- Application: Computer, Consumer Electronics.



Performance Curves

Dimensions Unit: mm



Specification:

Model	Rated Voltage	Operating Voltage	Rated Current	Input Power	Air Flow	Static Pressure	Speed	Noise	Weight
700512H	12VDC	10-14VDC	0.30A	1.24W	15.86CFM	2.87mm	4000RPM	26db	31g
700512M	12VDC	10-14VDC	0.12A	1.02W	17.92CFM	1.46mm	3500RPM	25db	31g
700512L	12VDC	10-14VDC	0.09A	1.20W	15.50CFM	1.36mm	3000RPM	26db	31g

Option: 24VDC Available


DC Fans

Xprovider Technology
Model: 7025 Series


- Fan Size: 70 x 70 x 25 mm
- Frame Material: Plastic P.B.T. UL 94V-0.
- Fan Blade Material: Plastic P.B.T. UL 94V-0.
- Lead Wire: UL 1007 AWG#24" 1/2' Red 1/2' Black.
- Bearing Type: Precision Ball or Quality sleeve.
- Application: Computer, Consumer Electronics.



Performance Curves



Dimensions Unit: mm



Specification:

Model	Rated Voltage	Operating Voltage	Rated Current	Input Power	Air Flow	Static Pressure	Speed	Noise	Weight
702512H	12VDC	10-14VDC	0.20A	2.40W	25.62CFM	2.85mm	3200RPM	28db	15g
702512M	12VDC	10-14VDC	0.15A	1.80W	21.79CFM	2.37mm	2700RPM	27db	15g
702512L	12VDC	10-14VDC	0.10A	1.20W	17.47CFM	1.89mm	2300RPM	25db	15g
Option: 24VDC Available									

DC Fans


Xprovider Technology

Model: 8015 Series


- Fan Size: 80 x 80 x 15 mm
- Frame Material: Plastic P.B.T. UL 94V-0.
- Fan Blade Material: Plastic P.B.T. UL 94V-0.
- Lead Wire: UL 1007 AWG#24"1/2" Red"1" Black.
- Bearing Type: Precision Ball or Quality sleeve.
- Application: Computer, Consumer Electronics.



Performance Curves



Dimensions Unit: mm



Specification:

Model	Rated Voltage	Operating Voltage	Rated Current	Input Power	Air Flow	Static Pressure	Speed	Noise	Weight
800512H	12VDC	9~14VDC	0.20A	1.12W	12.60CFM	2.77mm	3000RPM	11dB	11g
800512M	12VDC	9~14VDC	0.20A	1.44W	25.80CFM	1.73mm	2500RPM	29dB	11g
800512L	12VDC	9~14VDC	0.11A	1.20W	21.12CFM	1.32mm	2000RPM	27dB	11g

Option: 24VDC Available

DC Fans

Xprovider Technology



Model: 8020 Series

- Fan Size: 80 x 80 x 20 mm
- Frame Material: Plastic P.B.T. UL 94V-0.
- Fan Blade Material: Plastic P.B.T. UL 94V-0.
- Lead Wire: UL 1007 AWG#24"1/2" Red"1" Black.
- Bearing Type: Precision Ball or Quality sleeve.
- Application: Computer, Consumer Electronics.



Performance Curves

Dimensions Unit: mm



Specification:

Model	Rated Voltage	Operating Voltage	Rated Current	Input Power	Air Flow	Static Pressure	Speed	Noise	Weight
80202H	12VDC	9~14VDC	0.20A	2.40W	30.25CFM	2.57mm	3000RPM	31dB	32g
80202M	12VDC	9~14VDC	0.18A	2.16W	26.08CFM	2.31mm	2500RPM	29dB	32g
80202L	12VDC	9~14VDC	0.15A	1.80W	22.13CFM	2.36mm	2000RPM	27dB	32g

Option: 24VDC Available

DC Fans


Xprovider Technology

Model: 8025 Series


- Fan Size: 80 x 80 x 25 mm
- Frame Material: Plastic P.B.T. UL 94V-0.
- Fan Blade Material: Plastic P.B.T. UL 94V-0.
- Lead Wire: UL 1007 AWG#24" 1/2' Red 1/2' Black.
- Bearing Type: Precision Ball or Quality sleeve.
- Application: Computer, Consumer Electronics.



Performance Curves



Dimensions Unit: mm



Specification:

Model	Rated Voltage	Operating Voltage	Rated Current	Input Power	Air Flow	Static Pressure	Speed	Noise	Weight
802512H	12VDC	9-14VDC	0.25A	1.00W	41.15CFM	2.85mm	3000RPM	31dB	70g
802512M	12VDC	9-14VDC	0.18A	2.16W	35.19CFM	2.48mm	2500RPM	29dB	70g
802512L	12VDC	9-14VDC	0.15A	1.80W	30.25CFM	1.96mm	2000RPM	27dB	70g

Option: 24VDC Available

DC Fans

Xprovider Technology
Model: 9225 Series


- Fan Size: 92 x 92 x 25 mm
- Frame Material: Plastic P.B.T. UL 94V-0.
- Fan Blade Material: Plastic P.B.T. UL 94V-0.
- Lead Wire: UL 1007 AWG#24" 1/2" Red 1/2" Black.
- Bearing Type: Precision Ball or Quality sleeve.
- Application: Computer, Consumer Electronics.



Performance Curves



Dimensions Unit: mm



Specification:

Model	Rated Voltage	Operating Voltage	Rated Current	Input Power	Air Flow	Static Pressure	Speed	Noise	Weight
922512H	12VDC	9~14VDC	0.26A	4.92W	32.15CFM	3.86mm	3000RPM	42db	90g
922512M	12VDC	9~14VDC	0.23A	3.12W	46.53CFM	3.36mm	2500RPM	37db	90g
922512L	12VDC	9~14VDC	0.19A	2.52W	35.41CFM	2.77mm	2000RPM	36db	90g

Option: 24VDC Available

DC Fans


Xprovider Technology

Model: 12025 Series


- Fan Size: 120 x 120 x 25 mm
- Frame Material: Plastic P.B.T. UL 94V-0.
- Fan Blade Material: Plastic P.B.T. UL 94V-0.
- Lead Wire: UL 1007 AWG#24" 1/2' Red 1/2' Black.
- Bearing Type: Precision Ball or Quality sleeve.
- Application: Computer, Consumer Electronics.



Performance Curves



Dimensions Unit: mm



Specification:

Model	Rated Voltage	Operating Voltage	Rated Current	Input Power	Air Flow	Static Pressure	Speed	Noise	Weight
1202512H	12VDC	9-14VDC	0.41A	4.92W	64.52CFM	3.25mm	2400RPM	42db	140g
1202512M	12VDC	9-14VDC	0.26A	3.12W	62.17CFM	2.65mm	2000RPM	37db	140g
1202512L	12VDC	9-14VDC	0.21A	2.52W	66.57CFM	1.77mm	1600RPM	36db	140g

Option: 24VDC Available

Corevider Technology

Model: W8025 Series

- Fan Size: 80 x 80 x 25 mm
- Frame Material: Plastic P.B.T. UL 94V-0.
- Fan Blade Material: Plastic P.B.T. UL 94V-0.
- Lead Wire: UL 1007 AWG#24 "P" Red "N" Black.
- Bearing Type: Precision Ball or Quality sleeve.
- Application: Computer, Consumer Electronics.



Performance Curves

Dimensions: Unit: mm



Specification

Model	Rated Voltage	Operating Voltage	Rated Current	Input Power	Air Flow	Static Pressure	Speed	Noise	Weight
W602512B	12V/DC	10~14V/DC	0.25A	3.00W	12.36CFM	4.45mm	3000RPM	31dB	60g
W602512B	12V/DC	10~14V/DC	0.38A	4.72W	29.98CFM	2.89mm	2200RPM	29dB	60g
W602512L	12V/DC	10~14V/DC	0.5A	6.00W	36.32CFM	2.41mm	3000RPM	29dB	60g

Downloaded from jid.sagepub.com at UNIV OF CALIF SDIEGO on June 11, 2015